

TLP741J

OFFICE MACHINE
HOUSEHOLD USE EQUIPMENT
SOLID STATE RELAY
SWITCHING POWER SUPPLY

The TOSHIBA TLP741J consists of a photo-thyristor optically coupled to a gallium arsenide infrared emitting diode in a six lead plastic DIP package.


- Peak Off-State Voltage : 600V (Min.)
- Trigger LED Current : 10mA (Max.)
- On-State Current : 150mA (Max.)
- UL Recognized : UL1577, File No. E67349
- BSI Approved : BS EN60065 :1994
Certificate No. 6617
BS EN60950 :1992
Certificate No. 7366
- Isolation Voltage : 4000V_{rms} (Min.)
- Option (D4) type
VDE Approved : DIN VDE0884 / 08, 87
Certificate No. 65640

Maximum Operating Insulation Voltage : 630V_{PK}
Highest Permissible Over Voltage : 6000V_{PK}

(Note) When a VDE0884 approved type is needed,
please designate the “Option (D4)”


	7.62mm pich standard type	10.16mm pich (LF2) type
● Creepage Distance	: 7.0mm (Min.)	8.0mm (Min.)
Clearance	: 7.0mm (Min.)	8.0mm (Min.)
Insulation Thickness	: 0.5mm (Min.)	0.5mm (Min.)

Unit in mm



Weight : 0.35g

PIN CONFIGURATION (TOP VIEW)



- 1 : ANODE
- 2 : CATHODE
- 3 : N.C.
- 4 : CATHODE
- 5 : ANODE
- 6 : GATE

961001EAA2

● TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.

● The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.

● The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I_F	60	mA
	Forward Current Derating (Ta ≥ 39°C)	$\Delta I_F / ^\circ\text{C}$	−0.7	mA / °C
	Peak Forward Current (100μs pulse, 100pps)	I_{FP}	1	A
	Power Dissipation	P_D	100	mW
	Power Dissipation Derating (Ta ≥ 25°C)	$\Delta P_D / ^\circ\text{C}$	−1.0	mW / °C
	Reverse Voltage	V_R	5	V
	Junction Temperature	T_j	125	°C
DETECTOR	Peak Forward Voltage (R _{GK} = 27kΩ)	V_{DRM}	600	V
	Peak Reverse Voltage (R _{GK} = 27kΩ)	V_{RRM}	600	V
	On-State Current	I_T (RMS)	150	mA
	On-State Current Derating (Ta ≥ 25°C)	$\Delta I_T / ^\circ\text{C}$	−2.0	mA / °C
	Peak On-State Current (100μs pulse, 120pps)	I_{TP}	3	A
	Peak One Cycle Surge Current	I_{TSM}	2	A
	Peak Reverse Gate Voltage	V_{GM}	5	V
	Power Dissipation	P_D	150	mW
	Power Dissipation Derating (Ta ≥ 25°C)	$\Delta P_D / ^\circ\text{C}$	−2.0	mW / °C
	Junction Temperature	T_j	100	°C
Storage Temperature Range		T_{stg}	−55~125	°C
Operating Temperature Range		T_{opr}	−55~100	°C
Lead Soldering Temperature (10s)		T_{sol}	260	°C
Total Package Power Dissipation		P_T	250	mW
Total Package Power Dissipation Derating (Ta ≥ 25°C)		$\Delta P_T / ^\circ\text{C}$	−3.3	mW / °C
Isolation Voltage (AC, 1min., R.H. ≤ 60%)		BV_S	4000	V _{rms}

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V_{AC}	—	—	240	V _{ac}
Forward Current	I_F	15	20	25	mA
Operating Temperature	T_{opr}	−25	—	85	°C
Gate to Cathode Resistance	R_{GK}	—	10	27	kΩ
Gate to Cathode Capacity	C_{GK}	—	0.01	0.1	μF

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION		MIN.	TYP.	MAX.	UNIT
LED	Forward Voltage	V_F	$I_F = 10\text{mA}$		1.0	1.15	1.3	V
	Reverse Current	I_R	$V_R = 5\text{V}$		—	—	10	μA
	Capacitance	C_T	$V = 0, f = 1\text{MHz}$		—	30	—	pF
DETECTOR	Off-State Current	I_{DRM}	$V_{AK} = 600\text{V}$ $R_{GK} = 27\text{k}\Omega$	Ta = 25°C	—	10	5000	nA
				Ta = 85°C	—	1	150	μA
	Reverse Current	I_{RRM}	$V_{KA} = 600\text{V}$ $R_{GK} = 27\text{k}\Omega$	Ta = 25°C	—	10	5000	nA
				Ta = 85°C	—	1	150	μA
	On-State Voltage	V_{TM}	$I_{TM} = 100\text{mA}$		—	0.9	1.3	V
	Holding Current	I_H	$R_{GK} = 27\text{k}\Omega$		—	0.2	—	mA
	Off-State dv / dt	dv / dt	$V_D = 420\text{V}, R_{GK} = 27\text{k}\Omega$		—	10	—	V / μs
	Capacitance	C_j	$V = 0, f = 1\text{MHz}$	Anode to Gate	—	20	—	pF
				Gate to Cathode	—	350	—	

COUPLED CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I_{FT}	$V_{AK} = 6\text{V}, R_{GK} = 27\text{k}\Omega$	—	5	10	mA
Turn-on Time	t_{ON}	$I_F = 30\text{mA}, V_{AA} = 50\text{V}$ $R_{GK} = 27\text{k}\Omega$	—	10	—	μs
Coupled dv / dt	dv / dt	$V_S = 500\text{V}, R_{GK} = 27\text{k}\Omega$	500	—	—	V / μs
Capacitance (Input to Output)	C_S	$V_S = 0, f = 1\text{MHz}$	—	0.8	—	pF
Isolation Resistance	R_S	$V_S = 500\text{V}$	1×10^{12}	10^{14}	—	Ω
Isolation Voltage	BV_S	AC, 1 minute	4000	—	—	V_{rms}
		AC, 1 second, in oil	—	10000	—	
		DC, 1 minute, in oil	—	10000	—	V_{dc}

