



No.2834B

LA7221**VTR Electronic Switch**

The LA7221 is an electronic switch that was designed for use in audio video applications. It provides a wide dynamic range. The LA7221 has on-chip video clamp circuits (clamp elimination function).

Features


- Low-voltage (5V) operation.
- Three inputs selectable and muting function.
- Video clamp circuits on chip.
- Wide dynamic range (2.0Vp-p or greater).

Maximum Ratings at Ta = 25°C

			unit
Maximum Supply Voltage	V_{CC} max	7.0	V
Allowable Power Dissipation	P_d max	100	mW
Operating Temperature	T_{opr}	-10 to +70	°C
Storage Temperature	T_{stg}	-40 to +125	°C

Operatings Characteristics at Ta = 25°C, V_{CC} = 5.0V

		min	typ	max	unit
Operating Voltage	V_{CC} op	4.5	5.0	6.2	V
Current Dissipation	I_{CC}	3.5	4.6	6.6	mA
Maximum Input Level	V_{IN} max	2.0	2.2		Vp-p
Frequency Characteristic	G_F		0	±0.5	dB
Total Harmonic Distortion	THD		0.03	0.1	%
Crosstalk	CT	-70	-60		dB
Crosstalk Appearing in Muting Circuit	CT_m	-60	-50		dB
Output DC Offset	ΔV_{OUT}		5	15	mV
CTL Changeover Level	V_{CTL}	1.0	1.4	1.8	V
Differential Gain	DG		0.5	1.0	%
Differential Phase	DP		0.5	1.0	deg

Block Diagram and Application Circuit**Truth Table**


CTL.1	H	L	-	L
CTL.2	L	H	-	L
MUTE CTL	L	L	H	L
OUT	IN 1	IN 2	DC	IN 3

*: The output is indeterminate at other states than shown above.

Package Dimensions







(unit : mm)

3017C

**SANYO Electric Co., Ltd. Semiconductor Business Headquarters**

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

LA7221 Input / Output Configuration

Unit (resistance:Ω)					
Pin	Name	I/O Impedance or I/O Configuration		DC Voltage	Remarks
1	IN1	∞		2.4V	
2	CONTROL 1			0V	ON at 2.0V or greater
3	IN2	∞		2.4V	
4	CONTROL 2			0V	ON at 2.0V or greater
5	GND			0V	
6	IN3	∞		2.4V	
7	MUTE CONTROL			0V	ON at 2.0V or greater
8	OUT	20Ω	Emitter follower	1.0V	Collector current 1.6mA
9	V _{CC}			5.0V	

■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of **December, 1996**. Specifications and information herein are subject to change without notice.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.