

1	2	3	4	5	6	7	8	9	0
J	PW-P -3Xxx-LF			* Material : Nylon, UL 94V-2 * Integrally molded mounting ears available * Standard detent locking * 1,2,3,4,5,6,9,12,15 circuits available					
I	RoHS Compliant			LEADFREE					
H	15		12		9		6		
	7.5A		7.5A		9A		9A		
	250V		250V		250V		250V		
G									
F	24.6 0 (.9 69)		24.6 0 (.9 69)		24.5 0 (.9 65)		24.6 0 (.9 69)		
E	30.00 (1.181)		24.95 (.982)		19.80 (.780)		(.536) 13.61		
D									
C	18.7 8 (.7 39)		18.9 0 (.7 44)		18.3 0 (.7 20)		18.6 2 (.7 33)		
	5.03 (.198)		5.03 (.198)		5.03 (.198)		5.03 (.198)		
B	Промэлектроника		PART NO. PW-P-3Xxx		CHECKED BY CY		TOLERANCES ARE		
	Адрес для заказов: pr@promelec.ru		DWG NO. PW-P-3Xxx		DRAWING BY		DESCRIP TION:		
A			FILE NO.		PROJECTION		AREA		
	UNIT / mm		SCALE 1 : 1		.X ± 0.2 .XX ± .XXX ± AWG		REVISIONS		
							HK		
							DATE		