



PC816 Series

* Lead forming type (type) and taping reel type (P type) are also available. (PC816I/PC816P) (Page 656)

■ Features

1. High collector-emitter voltage (V_{CEO} : 70V)
2. Compact dual-in-line package
PC816 : 1-channel type
PC826 : 2-channel type
PC846 : 4-channel type
3. High isolation voltage between input and output (V_{ISO} : 5 000V_{rms})
4. Current transfer ratio
(CTR : MIN. 50% at $I_F=5\text{mA}$, $V_{CE}=5\text{V}$)
5. Recognized by UL, file No. E64380

■ Outline Dimensions





High Collector-emitter Voltage, High Density Mounting Type Photocoupler

■ Applications

1. Programmable controllers, computers
2. System appliances, measuring instruments
3. Signal transmission between circuits of different potentials and impedances

PC846



■ Absolute Maximum Ratings

(Ta = 25°C)

Parameter		Symbol	Rating	Unit
Input	Forward current	I _F	50	mA
	* ¹ Peak forward current	I _{FM}	1	A
	Reverse voltage	V _R	6	V
Output	power dissipation	P	70	mW
	Collector -emitter voltage	V _{C EO}	70	v
	Emitter-collector voltage	V _{E CO}	6	v
	Collector current	I _C	50	mA
	Collector power dissipation	P _C	150	mW
	Total power dissipation	P _{tot}	200	mW
	* ² Isolation voltage	V _{iso}	5000	V _{rms}
	Operating temperature	T _{opr}	-30 to + 100	°C
	Storage temperature	T _{stg}	-55 to + 125	°C
	* ³ Soldering temperature	T _{sod}	260	°C

*1 Pulse width $\leq 100 \mu\text{s}$, Duty ratio= 0.001

*240 to 60%RH, AC for 1 minute

*3 For 10 seconds

■ Electro-optical Characteristic

(Ta = 25°C)

Parameter		Symbol	Conditions	MIN.	TYP.	MAX	Unit	
Input	Forward voltage	V _F	I _F =20mA	—	1.2	1.4	v	
	Peak forward voltage	V _{FM}	I _{FM} =0.5A	—	—	3.0	V	
	Reverse current	I _R	V _R =4V	—	—	10	μA	
	Terminal capacitance	C _t	V=0, f=1kHz	—	30	250	pF	
output	Collector dark current	I _{C EO}	V _{CE} =20V, I _F =0	—	—	10 ⁻⁷	A	
Transfer characteristics	* ¹ Current transfer ratio	CTR	I _F =5mA, V _{CE} =5V	50	—	600	%	
	Collector -emitter saturation voltage	V _(CEsat)	I _F =20mA, I _C =1mA	—	0.1	0.2	v	
	Isolation resistance	R _{ISO}	DC500V, 40 to 60%RH	5×10 ¹⁰	1×10 ¹¹	—	Ω	
	Floating capacitance	C _f	V=0, f=1MHz	—	0.6	1.0	pF	
	Cut-off frequency	f _c	V _{CE} =5V, I _C =2mA, R _L =100Ω, -3dB	—	80	—	kHz	
	Response time	Rise time	t _r	V _{CE} =2V, I _C =2mA	—	4	18	μs
		Fall time	t _f	R _L =100 Ω	—	3	18	μs

*4 Classification table of current transfer ratio is shown below.

Model No.	Rank mark	CTR (%)
PC616A	A	80 to 160
PC816B	B	130 to 260
PC816C	c	200 to 400
PC816D	D	300 to 600
PC816AB	A or B	80 to 260
PC816BC	B or C	130 to 400
PC816CD	C or D	200 to 600
PC816AC	A, B or D	80 to 400
PC816BD	B, C or D	130 to 600
Pc616AD	A, B, C or D	80 to 600
PC816	A, B, C, D or So mark	50 to 600

**Fig. 1 Forward Current vs.
Ambient Temperature**




Fig. 2 Collector Power Dissipation VS. Ambient Temperature




Fig. 4 Forward Current vs. Forward Voltage




Fig. 6 Collector Current vs. Collector-emitter Voltage




Fig. 3 Peak Forward Current vs. Duty Ratio




Fig. 5 Current Transfer Ratio vs. Forward Current




Fig. 7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig. 8 Collector-emitter Saturation voltage vs. Ambient Temperature




Fig. 9 Collector Dark Current vs. Ambient Temperature




Fig. 10 Response Time vs. Load Resistance






Fig. 11 Frequency Response



Test Circuit for Response Time



Test Circuit for Frequency Response





Fig. 12 Collector-emitter Saturation Voltage vs. Forward Current



- Please refer to the chapter "Precautions for Use" (Page 78 to 93)